

**INTRODUCTION:**

The SerialComm CON-485-PI9 is an industrial high temperature grade bi-directional port powered RS-232 to RS-485 converter in a 9 pin format. It has a compact design for space restricted applications. It can convert any standard full duplex RS-232C port to any two-wire balanced half duplex RS-485 port. In simple terms, it will convert any RS-232 signal to a RS-485 signal and vice versa. The unit is powered from the RS-232 data lines. It also supports data direction auto-turnaround. Therefore, no external power or flow control is required. The data direction auto-turnaround automatically enables the RS-485 driver when data is present on the RS-232 side making the device plug-and-play, requiring no software drivers. The CON-485-PI9 has a DB9 female connector on the RS-232 side and 4-way terminal block on the RS-485 side. The high quality terminal block is friction plugged securely to the converter and can be removed and plugged back in.

**CERTIFICATIONS:**



**GENERAL FEATURES:**


- Port Powered: no external power is necessary
- Data Direction, auto-turnaround, no flow control is necessary
- Plug-and-Play (Device is hot-pluggable)
- 5 Year Manufacturer's Warranty
- RoHS, CE, FCC and ISO 9001 Compliance Certified
- Built-in surge protection, static protection and circuit protection
- Surface Mount RoHS Compliant Technology manufactured to ISO 9001 Standards

**PINOUT CONFIGURATION:**

**RS-232 SIDE - DB9 FEMALE**


SIGNAL	DCD	DTR	DSR	RTS	CTS	TX	RX	GND
PIN #	1	4	6	7	8	2	3	5
FUNCTION	TIED			TIED		TX	RX	GND

**FEM. DB9**



**RS-485 SIDE - ATTACHED TERMINAL BLOCK**

INDUSTRIAL CONVERTER  
High Sensitivity, 128 Drops, High Temp



**SPECIFICATIONS:**

PART NUMBER:	CON-485-PI9
STANDARDS:	EIA/TIA RS-232C Standard and RS-485 Standard
BAUD RATES:	From 300 Baud To 115,200 Baud
POWER SOURCE:	Port Powered From RS-232 Data Lines
CURRENT CONSUMPTION:	Less Than 10 mA
CONNECTOR TYPES:	RS-232 Side: DB9 Female and RS-485 Side: 4-Way Terminal Block
DISTANCE:	RS-232 Side: 16 ft (5m) and RS-485 Side: up to 4000 ft (1.2km)
MAX NUMBER OF DROPS:	128 Drops
STATIC PROTECTION:	1500W Static Protection
SURGE PROTECTION:	600W Surge Protection
WEIGHT:	0.8oz (23 grams)
DIMENSIONS:	2.80" X 1.33" X 0.66" (71.2 mm X 33.8 mm X 16.8 mm)
OPERATING TEMP.:	-40° F to 176° F (-40°C to 80° C)
OPERATING HUMIDITY:	5% To 95% - No Condensation

**TROUBLESHOOTING INSTRUCTIONS:**

Perform a loop back test on two CON-485-PI9 converters. Attach the two CON-485-PI9s to two serial ports on a PC and using two instances of a HyperTerminal program send a character from one and see if it echoes to the other. This will test both transmit and receive functions.

**APPLICATIONS:**




FIGURE 1: EXTENDING RS-232 DATA DISTANCE




FIGURE 2: MASTER/S�AVE MULTIPLE DROP CONFIGURATION